

303 Deadlock

The security features provided by the 303 Deadlock make it an ideal lockset for both domestic and commercial applications.

Features & Specifications

Suitable for hinged or sliding doors, the 303 features a strong interlocking case and mounting plate to resist jemmy attack, along with concealed fixing and a positive deadlocking action.

The mechanism and the design are protected by Australian and International Patents and Design Registrations.

Case

Thick walled, high purity zinc alloy casting. 121 mm wide, 76 mm high, 56 mm projection.

Backset

60 mm.

Bolt

Stainless steel.

Mounting Plate & Strike

Pressed steel.

Case Retainer Plate & Operating Mechanism

Solid pressed steel and zinc diecast components.

Door Thickness

30 to 45 mm.

Cylinders

5 pin tumbler mechanism inside and outside with brass cylinders and barrels.

Packing Plates

3 mm thick packing plates installed under lock body to align lock body with face of jamb.





Strike Conversion Plate

A strike conversion plate is required where the strike is to be installed in place of an existing flanges strike.

Keying

Standard

Supplied individually keyed with two keys per lock. 78,000 key combinations. Key blank KB2015P.

Special Keying

Can be keyed alike, master keyed, grand master keyed, maison keyed or construction keyed in Lockwood security keying systems.

Finishes

Standard

Gold Plated GLD
Satin Chrome SC
Bright Chrome CP
Brown BRN

Available in Trade and Display Pack.

303-N Single Cylinder Deadlock

Opened by key from outside and by turnknob from inside.





