


# FEATURES AND OPTIONAL FUNCTIONS

## With “thinking” backcheck (BC/ÖD)

Thanks to an innovative design concept, the resistance developed by this backcheck system as the door is opened beyond approx. 70° is directly proportional to door acceleration.

It is almost imperceptible when the door is opened slowly. However, if the door is opened hastily, the

backcheck responds in equal measure. And if the door should be flung open at speed – whether deliberately, thoughtlessly, accidentally or as a result of a gust of wind – the backcheck reacts at full strength, protecting the wall and door from damage.





- 1 Self-regulating backcheck
- 2 Infinitely variable closing speed in the range 180° – 70°  
70° – 15°
- 3 Infinitely variable closing speed in the range 15° – 0°
- 4 Adjustable latch range (by arm)

## With additional delayed action – Model BC/ÖD + DC/SV

This model with its additional, integrated delayed action enables the closing cycle to be retarded within an adjustable range from 180° – 70° so that disabled persons, mothers with prams and people carrying bulky items are able to pass through the door without difficulty.

This model can also be used for fire doors.




- 1 Adjustable delayed action
- 2 Fully controlled closing with adjustable speed

## With hold-open arm

Combining the TS 73 V with a hold-open arm enables the door to be held open at an appropriate angle (up to approx. 150°).

Hold-open arm with switch: The hold-open function can be switched on and off by the user by simply pressing a switch.



- 1 Hold-open range

**Hold-open arms are not permitted on fire doors**

# EASY TO FIT, ECONOMICAL AND WITH ADJUSTABLE CLOSING FORCE

Simple, easy installation, and guaranteed quality. Tested to EN 1154 Specially designed for internal doors, including fire doors, the DORMA TS 73 V is a universal solution for doors of differing designs and styles.

The flat and compact format of the TS 73 V means that there are practically no problems with installation; and tried and trusted quality is your assurance of reliability.

Certified to ISO 9001

## Plus points

### For the trade

- One model for all applications.
- Really practical solutions for special installation situations, thanks to the wide range of accessories.

### For the installer

- Quick and simple to fit. Closing force, closing speed, and latching action all set with just a few manual adjustments.
- Only one design for DIN-L and DIN-R doors, and for standard and framexing.

### For the designers

- Compact format in timeless design.
- Attractively-priced solution with optimum reliability.
- Wide range of applications.
- Anti-corrosive design for moist and damp areas.

### For the user

- Optimum wall and door protection thanks to "thinking" backcheck.
- Constant closing speed virtually unaffected by temperature fluctuations, with adjustable latch action.
- Smooth door action thanks to high mechanical efficiency.

Data and features		TS 73 V
Closing force adjustable	Size	EN 1-4
Standard doors <sup>1)</sup>	≤ 1100 mm	●
External doors, opening outwards <sup>1)</sup>		–
Fire and smoke control doors <sup>1)</sup>	≤ 1100 mm	●
Non-handed		●
Arm	Standard	●
	Flat form	○
	Slide channel	–
Closing force variable by means of adjustment screw		●
Closing speed adjustable at 3 separate valves	180° – 70°	●
	70° – 15°	●
	15° – 0°	●
Backcheck	self-regulating	●
	adjustable valve	●
Adjustable latching action	by arm	●
Delayed action		●
Hold-open		○
Weight in kg		1.7
Dimensions in mm	Length	245
	Overall depth	46
	Height	60
Door closer tested to EN 1154		●
CE mark for construction products		●
Approved to AS1905 Part 1 Fire Resistant Doors		●

● Yes – No ○ Option

<sup>1)</sup> For high and heavy doors, external doors, and for doors required to close against high wind pressure, we recommend DORMA TS 83.

