



STARTEC COMMERCIAL KEY IN LEVER
60, 70, 127mm Backset 85mm Rose



- > Features: Tested to 500,000 operating cycles
Tested to 3,600 (Newton Force) of latch strength
Tested to 200 hours of corrosion resistance
85mm rose can retrofit any existing Key-in-lever
- > Compliance: AS1428 Disability compliance
AS1905.1 & 1530.4 Fire resistance compliance
- > Door type: Timber or metal
- > Door thickness (mm): 35-50 (use spacer from 45-50mm)
- > Material: Chassis (Steel, zinc plated)
Lever (Zinc diecast)
Faceplate and Bolt (Stainless steel)
- > Strike Plate: Stainless steel 45mm, D and T types
- > Key Cylinder: C4 Häfele 6 pin keyway
Häfele restricted keying available
- > Finish: Satin chrome plated
- > Warranty: 10 Year Mechanical

Passage Lock




> Function: Both levers always unlocked

	Cat. No.
	911.83.724

Packing: 1 set

Privacy Lock




> Function: Push-button locking locks outside lever.
Turning inside lever releases button.
Outside lever has emergency release

	Cat. No.
	911.83.723

Packing: 1 set

Storeroom Lock




> Function: Outside lever fixed. Entrance by key only.
Inside lever always unlocked

	Cat. No.
Keyed to differ	911.83.725

Packing: 1 set

Entrance Lock




> Function: Turn/push-button locking, pushing and turning button locks outside lever requiring use of key until button is manually unlocked.
Push-button locking: pushing button locks outside lever until unlocked by key or by turning inside lever

	Cat. No.
Keyed to differ	911.83.729

Packing: 1 set

Classroom Lock




> Function: Outside lever locked and unlocked by key. Inside lever always unlocked

	Cat. No.
Keyed to differ	911.83.726

Packing: 1 set

Double Cylinder Lock




> Function: Key outside locks/unlocks both handles simultaneously. Key inside locks/unlocks both handles simultaneously

	Cat. No.
Keyed to differ	911.83.728

Packing: 1 set

Dummy Lever



> Function: Single lever fixed. Always unlocked with no latching function.

	Cat. No.
Keyed to differ	911.83.727

Packing: 1 set



Note:

Tested and approved for use with specific fire door types. Please enquire for further details.

Dimensions in mm Dimensional data not binding. We reserve the right to alter specifications without notice.