



The IS7085si is an aesthetic compact perimeter seal, specifically designed for 'clean room' applications. The highly resilient, smooth silicone rubber gasket allows for easy cleaning and assists in preventing the movement of air borne contaminants, whilst also contributing to reduced sound transmission.

This seal can be used to replace the door stop on both steel and timber door frames, where frames are non fire-rated.

Gap size

- Min. 0mm / max. 7mm

Door set standard lengths

- Single: 1 x 1000mm, 2 x 2100mm
- Long Single: 1 x 1000mm, 2 x 2750mm
- Double: 3 x 2100mm
- Long Double: 1 x 2100mm, 2 x 2750mm

Standard lengths

- 1000mm
- 2250mm
- Also available in: 250mm increments from 1000mm to 5000mm


Standard colours


- Silver anodised aluminium with grey silicone gasket and grey cover strip
- Black anodised aluminium with black silicone gasket and black cover strip

Fixing

- When fixing the IS7085si seal to rebated frames of single doors, specify a long back set door latch

Approval/s

- Fire tested to AS1530 Part 4 in accordance with AS1905 Part 1
-  Certifications GYI.R26629, GVWZ.R26629, GVWZ7.R26629
- Acoustically tested in accordance with AS1191, ISO140.3 and ISO10140-2



IS7085si

