

TOILET PARTITION HARDWARE




106

106 Gravity Hinge - Visible Fix

Specification

Material	Diecast Zinc, Alloy ZP3 #304 Stainless Steel Shaft Nylon Inserts
Finish	SCP: Satin Chrome Plate BCP: Bright Chrome Plate (Hold Open Available Only)
Mounting	Screw Fix
Minimum Hinge Clearance for Lift-Off Hinges	30mm
Specify	106_LHHC: Left Hand, Hold Closed. Assists door to move towards Hold Closed position 106_LHHO: Left Hand, Hold Open. Assists door to move towards Hold Open position 106_RHHC: Right Hand, Hold Closed. Assists door to move towards Hold Closed position 106_RHHO: Right Hand, Hold Open. Assists door to move towards Hold Open position
Features	Gravity-assisted door opening/door closing with lift-off capability.
Load Rating	15Kg per hinge For optimum performance - 2 hinges per door up to 30Kgs For doors over 30Kg allow for 15Kg per hinge Note: 3 Hinges per door is recommended to prevent door bowing
Disclaimer	Gravity hinges contain no mechanical components. The functionality of these hinges can vary depending on the environment. When selecting this product, please view our Product Disclosure Statement in the Care and Maintenance Download below.



Downloads & Resources

- Care & Maintenance
- Installation instructions
- Associated Videos
- Stainless Steel Cleaning & Maintenance
- Accessibility and safety features of Metlam Australia Toilet Partition Hardware and how to use them
- Troubleshooting your Metlam Australia Toilet Partition Hardware - Hinges

The photographs and line drawings of the products presented above are representational only. Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.