

Door Frame / Perimeter Seals



RP94Si



A weather and acoustic seal, suitable for rebated frames. RP94Si is quick and easy to install, either mitred or butt jointed to the head and jambs without removing the door. Slotted for installation adjustment, the soft silicon bulb accommodates a tighter seal and with a tamper proof cover strip, provides a fit and forget feature.

Can be used in conjunction with Raven door bottom seals, astragals and threshold plates.

Note: The tamper proof aluminium cover strip is not recommended for removal once installed. Refer to RP78Si or RP10Si for this feature.

Location: Head and jambs of single and double butt hinged doors.

Min/Max Gap: 0mm to 6mm.

Finish:* Satin clear (silver), bronze or black anodised aluminium (15µm) or paint at extra cost (cover strip only).

Fixing: Screw fix. Zinc plated, cross recess head S.T. screws and cover strip supplied.

Seal: RP394Si. Grey or black silicon rubber (SE).

Sizes: Available in door set sizes or stock lengths.

Approvals

UL R37913.

Certifire CF 5710.

Acoustic AUS/NZ: NCC F7D6.

UK/EU: Approved Document E. Rated to BS EN ISO 717-1.

Fire AUS/NZ: NCC S12C2. AS1530.4 & AS 1905.1. NZBC C/AS2 4.16.2.

UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

Up to FRL / FRR-/240/30 & FD240. 🔥

Gasket flammability index 1 when tested to AS1530.2.

Smoke NCC S12C4. AS1530.7 & BS EN 1634-3. Meets smoke leakage rates specified in AS6905 & EN 13501-2 "Sa" "S₂₀₀".

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Certification

Global GreenTag Cert™

Product Health Declaration™

(GreenTag PHD™)

PlatinumHEALTH™ HealthRATE™



© Raven Products Pty Ltd

*Note: Not all finishes are available in all sizes.

RP113



A timber door stop frame seal suitable for plain or rebated frames.

Can be used in conjunction with Raven door bottom seals and astragals.

Note: If fixing to rebated frames of single doors, specify a long backset door latch.

Location: Head and jambs of single and double butt hinged doors.

Min/Max Gap: 0mm to 7mm. (Compression 1mm to 3mm).

Finish:* Genuine plantation Tasmanian oak.

Fixing: Nail fix. Zinc plated nails supplied.

Seal: RP320. Brown silicon rubber.

Sizes: Available in single and double door set sizes.

Approvals


Acoustic AUS/NZ: NCC F7D6.

UK/EU: Approved Document E. Rated to BS EN ISO 717-1.

Smoke AUS/NZ: NCC S12C4. NZBC C/AS2 4.16.2(b).

UK/EU: Approved Document B.

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.



© Raven Products Pty Ltd