Door Bottom Sweep Seals



RP17b











Co-extrusion (Adhesive backed).

A co-extruded PVC sweep seal that fits to the stiles or bottom of doors. These extremely flexible seals can be quick and easily installed without removing the door. Ideal for sliding and security screen doors.

Can be used in conjunction with Raven RP13 and RP82 threshold plates.

Location: Bottom of or around sliding or outward opening butt hinged doors.

Min/Max Gap: Up to 19mm (user determined).

Fixing: Self-adhesive or can be screw fixed.

Note: Contact surface must be clean, smooth and if painted, well cured. Selfadhesive seals will not adhere to oiled or alkyd finishes or to easy clean wash and wear paint surfaces.

Seal: White and grey or brown rigid and flexible PVC.

Sizes: Available in stock lengths.

Approvals


Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.


Insects/Vermin AS4674, 2.1.5(iv), 2.1.7.

Certification

Global GreenTag^{CertTM}

Product Health Declaration™ (GreenTag PHD™) PlatinumHEALTH™ HealthRATE™







RP26


















The RP26 is ideal for use in conjunction with Raven threshold plates.

Location: Bottom of single and double, outward opening, butt hinged doors, tilt up doors or can be used as an astragal seal.

Min/Max Gap: 5mm to 20mm (user determined).

Finish:* Satin clear (silver), bronze anodised aluminium (15µm) or paint at extra cost.

Fixing: Concealed screw fix. Zinc plated, cross recess head S.T. screws and cover strip supplied. Fixing holes are pre-slotted.

Seal: RP326. Black EPDM.

Sizes: Available in stock lengths.

Approvals

Fire AUS/NZ: NCC S12C2. AS1530.4 & AS 1905.1.

UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

Up to FRL / FRR-/120/30 & FD120.

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Insects/Vermin AS4674, 2.1.5(iv), 2.1.7.

Certification

Global GreenTag^{CertTM}

Product Health Declaration™ (GreenTag PHD™) PlatinumHEALTH™ HealthRATE™

