

Threshold Plates



RP27



A heavy duty threshold plate designed for sill and carpet edge protection.

Can be used in conjunction with Raven door bottom seals to prevent rain, draughts, noise and smoke infiltration.

Location: Door sill.

Finish:* Satin clear (silver) anodised aluminium (25µm).

Fixing: Screw fix. Colour matched zinc plated, cross recess head CSK S.T. screws supplied.

Sizes: Available in stock lengths.

Approvals

ANSI/BHMA A156.21

Access & Mobility NZ: NZBC D1/AS1 1.3.2.

UK/EU: Approved Document M.

Fire AUS/NZ: NCC S12C2. AS1530.4 & AS 1905.1. NZBC C/AS2 4.16.2(a) & App C6.1.1.

UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

Up to FRL / FRR-/240/30.

BAL ≤FZ BAL FZ when used with a BAL rated door bottom seal in accordance with AS 3959.


Certification

Global GreenTag^{Cert™}

Product Health Declaration™

(GreenTag PHD™)

PlatinumHEALTH™ HealthRATE™



*Note: Not all finishes are available in all sizes.

RP28



RP28 is a wide, heavy duty threshold plate with a ribbed profile and integral sill gaskets. They are ideal for use with pivot hinge doors.

Can be used in conjunction with Raven door bottom seals to prevent rain, draughts, noise and smoke infiltration.

Location: Door sill.

Finish:* Satin clear (silver) anodised aluminium (25µm).

Fixing: Screw fix. Colour matched zinc plated, cross recess head CSK S.T. screws supplied.

Seal: RP404a. Grey flexible PVC.

Sizes: Available in stock lengths.

Approvals

ANSI/BHMA A156.21

Access & Mobility NZ: NZBC D1/AS1 1.3.2.

UK/EU: Approved Document M.

Fire AUS/NZ: NCC S12C2. AS1530.4 & AS 1905.1. NZBC C/AS2 4.16.2(a) & App C6.1.1.

UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

Up to FRL / FRR-/240/30 & FD120.

BAL ≤FZ BAL FZ when used with a BAL rated door bottom seal in accordance with AS 3959.

Certification

Global GreenTag^{Cert™}

Product Health Declaration™

(GreenTag PHD™)

PlatinumHEALTH™ HealthRATE™

