

Door Bottom Sweep Seals



RP30, RP31



The RP30 and RP31 are heavy duty sweep/compression seals. The RP30 is fitted into a concealed, machined groove that should be deep enough to allow packing for adjustment. Forms a weather seal when used with Raven RP13 or RP82 threshold plates.

The RP31 has greater compression than the RP30 and the design does not allow adjustment so it should not be installed in situations where adjustability is required. Forms a weather seal when used with Raven RP82 or RP115 threshold plates.

Location: Bottom of doors, meeting stiles or user determined bumper strip.

Min/Max Gap:

RP30 3mm to 8mm (user determined).

RP31 12mm to 17mm (user determined).

Finish:*

RP30 Satin clear (silver), bronze anodised aluminium (15µm) or paint at extra cost.

RP31 Satin clear (silver) anodised aluminium (15µm) or paint at extra cost.

Fixing: Concealed screw fix. Zinc plated, cross recess head S.T. screws supplied.

Seal:

RP30 RP330. Black EPDM.

RP31 RP331. Black EPDM.

Sizes: Available in stock lengths.

Approvals

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Insects/Vermin AS4674, 2.1.5(iv), 2.1.7.

Certification

Global GreenTag Cert™

Product Health Declaration™ (GreenTag PHD™)

PlatinumHEALTH™ HealthRATE™

*Note: Not all finishes are available in all sizes.

RP51Si



A heavy duty silicon rubber sweep seal for the bottom of outward opening doors. RP51Si has slotted fixing holes for adjustment with a push-in cover strip for concealed fixing.

The RP51Si is ideal for use in conjunction with Raven threshold plates.

Location: Bottom of single and double, outward opening, butt hinged doors, tilt up doors or can be used as an astragal seal.

Min/Max Gap: 5mm to 20mm (user determined).

Finish:* Satin clear (silver), bronze anodised aluminium (15µm) or paint at extra cost.

Fixing: Concealed screw fix. Zinc plated, cross recess head S.T. screws and cover strip supplied. Fixing holes are pre-slotted.

Seal: RP351Si. Grey silicon rubber (SE).

Sizes: Available in stock lengths.

Approvals

UL R37913.

Certifire CF 5710.

Fire & Smoke AUS/NZ: NCC S12C2. AS1530.4 & AS 1905.1. NZBC C/AS2 4.16.2 & App C6.1.1 & App C6.1.2.


UK/EU: Approved Document B. BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

Up to FRL / FRR-120/30 & FD120. Gasket flammability index 1 when tested to AS1530.2.

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Insects/Vermin AS4674, 2.1.5(iv), 2.1.7.

RP30



RP31

