


The seals below are superior quality, self-adhesive weather-strip seals for doors and windows. Quick and easy to install, they are DIY products which work well in eliminating draughts, rattles and cushioning applications.

RP14









Seal: White or grey open cell urethane foam.

easy clean wash and wear paint surfaces.

Sizes: 5m coil.

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

RP14b







Location: Perimeter of doors and windows. Min/Max Gap: 8mm to 11mm (user determined).

Fixing: Self-adhesive. Note: Contact surface must be clean, smooth and if painted, well cured. Self-adhesive seals will not adhere to oiled or alkyd finishes or to easy clean wash and wear paint surfaces.

Seal: White open cell urethane foam.

Sizes: 2.5m coil.

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

RP48

















Location: Perimeter of doors and windows.

Min/Max Gap: 3mm to 5mm (user determined). Fixing: Self-adhesive. Note: Contact surface must be

clean, smooth and if painted, well cured. Self-adhesive seals will not adhere to oiled or alkyd finishes or to easy clean wash and wear paint surfaces.

Seal: White, brown or grey EPDM closed cell sponge. Sizes: 5m coil pack (2 x 2.5m), jumbo reel

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Certification

Global GreenTag^{CertTM}

Product Health Declaration™ (GreenTag PHD™) PlatinumHEALTH™ HealthRATE™

RP108



















Location: Multi-purpose (user determined).

Min/Max Gap: 6mm to 8mm (user determined). Fixing: Self-adhesive. Note: Contact surface must be clean, smooth and if painted, well cured. Self-adhesive seals will not adhere to oiled or alkyd finishes or to

easy clean wash and wear paint surfaces. Seal: White or grey EPDM closed cell sponge.

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Product Health Declaration™ (GreenTag PHD™)

Certification

Global GreenTag^{CertTM}

Sizes: 2m coil pack.

RP14a







Location: Perimeter of doors and windows.

Min/Max Gap: 3mm to 5mm (user determined).

Fixing: Self-adhesive. Note: Contact surface must be clean, smooth and if painted, well cured. Self-adhesive seals will not adhere to oiled or alkyd finishes or to easy clean wash and wear paint surfaces.

Seal: White or grey open cell urethane foam.

Sizes: 5m coil.

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

RP61



12









Location: Perimeter of doors and windows.

Min/Max Gap: 3mm to 5mm (user determined).

Fixing: Self-adhesive. Note: Contact surface must be clean, smooth and if painted, well cured. Self-adhesive seals will not adhere to oiled or alkyd finishes or to easy clean wash and wear paint surfaces.

Seal: Grey polypropylene.

Sizes: 5m coil.

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

RP59



















Location: Perimeter of doors and windows.

Min/Max Gap: 2mm to 4mm (user determined).

Fixing: Self-adhesive. Note: Contact surface must be clean, smooth and if painted, well cured. Self-adhesive seals will not adhere to oiled or alkyd finishes or to easy clean wash and wear paint surfaces.

Seal: White, brown or grey EPDM closed cell sponge. Sizes: 5m coil pack (2 x 2.5m), jumbo reel

Approvals: Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.

Certification

Global GreenTag^{CertTM}

Product Health Declaration™ (GreenTag PHD™) PlatinumHEALTH™ HealthRATE™

