

RP7



A rigid and flexible PVC door frame seal suitable for rebated timber frames. The RP7 rigid section can be painted. Used in conjunction with Raven door bottom seals and astragals.

Location: Timber head and jambs of single and double butt hinged doors.

Min/Max Gap: 0mm to 7mm (compression 1mm to 3mm).


Fixing: Nail fix. Zinc plated nails supplied.

Seal: White or brown rigid and flexible PVC. Can be painted.

Sizes: Available in single door sets.

Approvals

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.



© Raven Products Pty Ltd

RP10



An effective acoustic door stop frame seal which is quick and easy to install on plain or rebated door frames. Multi-fin design for improved noise and energy sealing. The minimum deflection design creates maximum sealing efficiency. RP10 can be mitred or butt jointed for a neat finish. Adjustable by large concealed fixing slots for a precision fit. RP10 has a tamper resistant, rigid PVC cover strip (SE). Can be used on all four sides of the door to form a bulkhead seal.

Note: If fixing to rebated frames of single doors, specify a long backset door latch.

Location: Head and jambs of single and double butt hinged doors.

Min/Max Gap: 0mm to 10mm.

Finish:* Satin clear (silver), bronze anodised aluminium (15µm) or paint at extra cost.

Fixing: Screw fix. Zinc plated, cross recess head S.T. screws supplied.

Seal: RP410. Black flexible PVC. Black rigid flexible PVC (SE) cover strip.

Sizes: Available in door set sizes or stock lengths.

**Note: Not all finishes are available in all sizes.*

Approvals


Acoustic AUS/NZ: NCC F7D6.
UK/EU: Approved Document E. Rated to BS EN ISO 717-1.

Fire AUS/NZ: NCC Spec. C3.4.
AS1530.4:2005 & earlier. NZBC C/AS2 4.16.2.

UK/EU: Approved Document B.
BS 476 Pt. 20 & 22 (similar to BS EN 1634-1).

Up to FRL / FRR-/240/30 & FD240. 🔥

Energy ABCB Housing Provisions Standard 2022 13.4.4 & NCC J5D5.



© Raven Products Pty Ltd